







Blue Layflat Discharge Hose



PVC layflat hose is a flexible hose with high tensile polyester filament with abrasion and ozone resistant cover. Features anti-aging properties, no smell, and long life. Environmental grade hose can meet REACH standard. Anti-UV. Easy to use and transport.

- ▶ **APPLICATIONS:** *Agriculture, Construction, Irrigation, Dewatering*
- ▶ **SAFETY FACTOR:** *3:1*
- ▶ **MATERIAL:** *PVC*
- ▶ **TEMPERATURE:** *23°F to 149°F (Constant Operation)*




Part Number	 I.D.	 Length	 Working Pressure	 Lbs./Ft.
AH-1.5-LF-BLUE	1-1/2"	300 FT	80 PSI	0.15 LBS/FT
AH-2-LF-BLUE	2"	300 FT	80 PSI	0.20 LBS/FT
AH-2.5-LF-BLUE	2-1/2"	300 FT	70 PSI	0.29 LBS/FT
AH-3-LF-BLUE	3"	300 FT	70 PSI	0.34 LBS/FT
AH-4-LF-BLUE	4"	300 FT	70 PSI	0.54 LBS/FT
AH-6-LF-BLUE	6"	300 FT	60 PSI	1.08 LBS/FT
AH-8-LF-BLUE	8"	300 FT	35 PSI	1.48 LBS/FT







Blue Layflat Discharge Hose

POPULAR ASSEMBLIES



Part Number	 Size & Length	 Ends	 Attaching Method
PA-2-LF-BLUE-C-E-50FT	2" X 50 FT	CAMLOCKS	CRIMPED
PA-3-LF-BLUE-C-E-50FT	3" X 50 FT	CAMLOCKS	CRIMPED
PA-4-LF-BLUE-C-E-50FT	4" X 50 FT	CAMLOCKS	CRIMPED
PA-6-LF-BLUE-C-E-50FT	6" X 50 FT	CAMLOCKS	CRIMPED



Part Number	 Size & Length	 Ends	 Attaching Method
PA-2-LF-BLUE-PINLUG-50FT	2" X 50 FT	PINLUGS	CRIMPED
PA-3-LF-BLUE-PINLUG-50FT	3" X 50 FT	PINLUGS	CRIMPED
PA-4-LF-BLUE-PINLUG-50FT	4" X 50 FT	PINLUGS	CRIMPED