Diamondback
HYDRAULIC HOSE

DIN-EN 4SH - Wrapped Black

Extra high pressure hydraulic lines 3626 to 6092 PSI and hydrostatic transmission lines for use with petroleum, synthetic or water based fluids in hydraulic systems. Suitable for earthmoving & material handling equipments and machineries/systems.

TUBE	*Black colour, synthetic rubber resistant to oil and water*
REINFORCEMENT	*Four high tensile steel wire spirals*
COVER	*Black colour, synthetic rubber resistant to abrasion and weather, oil & ozone*
TEMPERATURE	*-40°F to +212°F (Continuous - Intermittent: +248°F)*

Part Number	I.D. *(inch)*	O.D. *(inch)*	Working Pressure *(PSI)*	Burst Pressure *(PSI)*	Minimum Bend Radius *(inch)*	Length *(feet)*	Weight *(Lbs/Ft)*
AH-4SH-12	3/4"	1.27"	6000 PSI	24000 PSI	11"	100-200'	1.62 Lbs
AH-4SH-16	1"	1.52"	5500 PSI	22000 PSI	13"	100-200'	2.12 Lbs
AH-4SH-20	1-1/4"	1.79"	5000 PSI	20000 PSI	18"	100'	2.55 Lbs
AH-4SH-24	1-1/2"	2.11"	4250 PSI	17000 PSI	22"	100'	3.26 Lbs
AH-4SH-32	2"	2.68"	3500 PSI	14000 PSI	27"	100'	4.92 Lbs

POWERTRACK USA

nationalsales@powertrackhose.com