

The PVC layflat hose is made of high strength polyester filament and high quality PVC. Hose offers great resistance and is lightweight, making layflat hose easy to use and transport. Layflat hose can be used as main hose of irrigation system and is designed for water discharge for long lasting service.

PVC/Nitrile - Popular due to being heavy duty and is the best choice for rough conditions. PVC Nitrile Layflat hoses are widely used in water discharge, drainage, irrigation installations, pumping of sludge and liquid fertilizers, chemical industry, mining, etc.

| Part Number | I.D. | l———I ← → Length | Coupling | Working Pressure | Burst Pressure | Lbs./PC. |
|----------------------------|------|------------------------|----------|------------------|----------------|----------|
| BLUE PVC LAYFLAT ———— | | | | | | |
| PA-2-LF-BLUE-C-E-50FT | 2″ | 50 feet | CAMLOCK | 90 PSI | 270 PSI | 11.9 |
| PA-3-LF-BLUE-C-E-50FT | 3″ | 50 feet | CAMLOCK | 90 PSI | 270 PSI | 20.72 |
| PA-4-LF-BLUE-C-E-50FT | 4" | 50 feet | CAMLOCK | 60 PSI | 180 PSI | 31.31 |
| RED PVC LAYFLAT | | | | | | |
| PA-3-LF-RED-C-E-50FT | 3″ | 50 feet | CAMLOCK | 120 PSI | 360 PSI | 26.23 |
| BLACK PVC/NITRILE LAYFLAT | | | | | | |
| PA-4-LF-BLACK-C-E-50FT | 4" | 50 feet | CAMLOCK | 150 PSI | 450 PSI | 45.19 |
| PA-6-LF-BLACK-C-E-50FT | 6″ | 50 feet | CAMLOCK | 150 PSI | 450 PSI | 81.57 |
| YELLOW PVC/NITRILE LAYFLAT | | | | | | |
| PA-4-LF-YELLOW-C-E-50FT | 4" | 50 feet | CAMLOCK | 150 PSI | 450 PSI | 45.19 |
| PA-6-LF-YELLOW-C-E-50FT | 6″ | 50 feet | CAMLOCK | 150 PSI | 450 PSI | 81.57 |