









PHOENIX BLOWOUT PREVENTER HOSE

Phoenix Blowout Preventer Hoses (BOP) are developed for control of high-pressure, fire-resistant and heat-insulation. Mainly used for the hydraulic control of the BOP for drilling and for hydraulic transmission at high temperature and flammable places in the metallurgic industry.



Complies with American Petroleum Industry API 16D SY/T5053.2-200 standards and Lloyd's 1000/499 Fire Test.

- ▶ **TUBE:** *Black, oil resistant Nitrile*
- ▶ **REINFORCEMENT:** *Multiple plies of high tensile steel wire braids or spirals*
- ▶ **COVER:** *Red oil and abrasion resistant Chloroprene, flame resistant*
- ▶ **TEMPERATURE:** *-40°F to + 212°F*

Part Number	 I.D. (inch)	 O.D. (inch)	 Working Pressure (PSI)	 Burst Pressure (PSI)	 Bend Radius (inch)	 Lbs./Ft.
AH-16-BOP-5K	1"	1.96"	5,000 PSI	15,000 PSI	14.2"	2.0 Lbs/Ft
AH-24-BOP-5K	1-1/2"	2.28"	5,000 PSI	15,000 PSI	22.0"	3.4 Lbs/Ft
AH-32-BOP-10K	2"	3.38"	10,000 PSI	22,500 PSI	37.4"	7.4 Lbs/Ft

POWERTRACK

nationalsales@powertrackhose.com