PYTHON Composite Hose

Introducing Python - Powertrack's Composite Hose, your solution for suction and discharge applications when weight and flexibility matter! Python is available in 10' and 20' premade lengths, they are tested and come with certification, guaranteeing their quality and performance. With its composite construction, Python offers excellent durability, chemical resistance, and flexibility. Choose Python for reliable and efficient fluid transfer in various industries.

CONSTRUCTION

INNER WIRE SPIRAL: Galvanized Steel (G)
 OUTER WIRE SPIRAL: Galvanized Steel (G)
 INNER LINING: Polypropylene (E)
 COVER: PVC (PP on request)

FEATURES

► NORMS: EN 13765: 2018 ► TEMPERATURE RANGE: -22°F to +212°F.

SAFETY FACTOR: 4:1
VACUUM: 13 PSI

LENGTH COILS: 98 Ft. Other under request.

ENDS: Galvanized Steel 150lb Fixed x Floating or Victaulic.

ANSI 150 LB RF (raised face) fixed by floating flange

Part Number	I.D. (inch)	O.D. (inch)	Working Pressure (PSI)	Burst Pressure (PSI)	Bend Radius (inch)	Lbs./Ft.
PA-6-PYTHON-FIX-FLOAT-10FT	6″	7.36"	250 PSI	1,000 PSI	19.56"	8.0 Lbs/Ft
PA-6-PYTHON-FIX-FLOAT-20FT	6″	7.36"	250 PSI	1,000 PSI	19.56"	8.0 Lbs/Ft
PA-8-PYTHON-FIX-FLOAT-10FT	8″	9.09"	250 PSI	1,000 PSI	29.13"	14.44 Lbs/Ft
PA-8-PYTHON-FIX-FLOAT-20FT	8″	9.09"	250 PSI	1,000 PSI	29.13"	14.44 Lbs/Ft
PA-10-PYTHON-FIX-FLOAT-10FT	10″	11.37"	250 PSI	1,000 PSI	36.22"	16.79 Lbs/Ft
PA-10-PYTHON-FIX-FLOAT-20FT	10″	11.37"	250 PSI	1,000 PSI	36.22"	16.79 Lbs/Ft
PA-12-PYTHON-FIX-FLOAT-10FT	12"	13.46″	200 PSI	800 PSI	45.27	18.81 Lbs/Ft
PA-12-PYTHON-FIX-FLOAT-20FT	12"	13.46"	200 PSI	800 PSI	45.27	18.81 Lbs/Ft
PA-10-PYTHON-VIC-VIC-10FT	10″	11.37"	250 PSI	1,000 PSI	36.22"	16.79 Lbs/Ft
PA-10-PYTHON-VIC-VIC-20FT	10″	11.37"	250 PSI	1,000 PSI	36.22"	16.79 Lbs/Ft
PA-12-PYTHON-VIC-VIC-10FT	12"	13.46″	200 PSI	800 PSI	45.27	18.81 Lbs/Ft
PA-12-PYTHON-VIC-VIC-20FT	12"	13.46"	200 PSI	800 PSI	45.27	18.81 Lbs/Ft