







# Wolverine

## OILFIELD VAC HOSE



Oilfield vacuum trucks and tank trucks, designed for situations demanding full service or specific working pressures. Well-suited for various applications, such as the handling of crude oil, saltwater, freshwater, tank bottoms, drilling mud, diluted hydrochloric acid solutions, diesel fuels, and sewage transfer.

- ▶ **TUBE:** *Black Nitrile synthetic rubber RMA class A (High Oil Resistance)*
- ▶ **REINFORCEMENT:** *Spiral-plyed synthetic fabric with helix wire*
- ▶ **COVER:** *Black abrasion, oil, weather & ozone resistant rubber (Corrugated)*
- ▶ **TEMPERATURE:** *-20°F to +180°F*
- ▶ **SAFETY FACTOR:** *4:1*
- ▶ **VACUUM:** *29inHG*

Part Number	 I.D. (inch)	 O.D. (inch)	 Working Pressure (PSI)	 Standard Length (feet)	 Bend Radius (inch)	 Lbs./Ft.
AH-1-OSD	1"	1.46"	150 PSI	100'	6"	0.59 Lbs/Ft
AH-1.25-OSD	1-1/4"	1.73"	150 PSI	100'	8"	0.74 Lbs/Ft
AH-1.5-OSD	1-1/2"	1.97"	150 PSI	100'	12"	0.85 Lbs/Ft
AH-2-OSD	2"	2.56"	150 PSI	100'	16"	1.38 Lbs/Ft
AH-2.5-OSD	2-1/2"	3.03"	150 PSI	100'	18"	1.64 Lbs/Ft
AH-3-OSD	3"	3.62"	150 PSI	100'	20"	2.27 Lbs/Ft
AH-4-OSD	4"	4.76"	150 PSI	100'	28"	3.61 Lbs/Ft
AH-6-OSD	6"	6.85"	150 PSI	100'	47"	6.22 Lbs/Ft

# POWERTRACK<sup>USA</sup>

[nationalsales@powertrackhose.com](mailto:nationalsales@powertrackhose.com)